

CLAIMS

1. Improved efficiency impact absorption device (10, 10'), of the type comprising a honeycomb (20), where the above-mentioned honeycomb (20) features a
5 number of ribs (11) that define respective outlets (12), having a preferably hexagonal section, terminating in holes (13), in the lower part of the honeycomb (20), the above-mentioned honeycomb (20) being injection-moulded in plastic, characterised in
10 that the above-mentioned plastic can be plastic resin derived from polycarbonate or rubber-filled polypropylene.

2. Device (10, 10'), as in claim 1, characterised in that the above-mentioned plastic
15 resin derived from polycarbonate is Xenoy®.

3. Device (10, 10'), as in claim 1 or 2, characterised in that the above-mentioned honeycomb features a taper at at least one of its longitudinal ends.

20 4. Device (10, 10'), as in claim 1, characterised in that it is combined with a deformation containment element wrapped around the above-mentioned tapered end.

5. Device (10, 10'), as in claim 4,
25 characterised in that the above-mentioned containment element is made of high resistance material, preferably

steel.

6. Device (10, 10'), as in claim 4 or 5,
characterised in that the above-mentioned containment
element is made integral with the related honeycomb
5 (20).

7. Device (10, 10'), as in claim 4,
characterised in that the above-mentioned containment
element is obtained directly on the vehicle.

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100